

One Way Shut-Off 

34 SCFM 



PLUG
(STEEL)

♦ **AUTOMATIC**
COUPLER
(STEEL/BRASS)

♦ **MANUAL**
COUPLER
(STEEL/BRASS)

MANUAL
COUPLER
(BRASS)

Applications

- Ideal for : Air tools
- Vacuum
- Water

Features

- Interchangeable with 1/4" ARO Type plugs
- Corrosion resistant

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)

Air Flow

34 SCFM

Construction

Body : Steel



Sleeve and Valve Spring : Stainless Steel

Seal : Buna-N

Locking Balls : Stainless Steel



Socket Sleeve : Steel

FEMALE THREAD




	Part No.	Part No.	Part No.	Part No.
1/8" (F) NPT	-	17.1422	17.1722	-
1/4" (F) NPT	17.1142	17.1442	17.1742	17.1743
3/8" (F) NPT	-	17.1462	17.1762	17.1763

MALE THREAD



	Part No.	Part No.	Part No.	Part No.
1/8" (M) NPT	17.1222	-	17.1822	17.1823
1/4" (M) NPT	17.1242	17.1542	17.1842	17.1843
3/8" (M) NPT	-	17.1562	17.1862	17.1863

HOSE BARB



	Part No.	Part No.	Part No.	Part No.
1/4" I.D.	17.1342	17.1642	17.1942	17.1943
5/16" I.D.	17.1352	17.1652	17.1952	17.1953
3/8" I.D.	17.1362	17.1662	17.1962	17.1963

2 OR 4 PIECES KIT

Part No. Description

17.1711C 2 pieces kit (17.1242 + 17.1742)

17.1704C 4 pieces kit

(17.1142 + 17.1242 + 17.1742 + 33.1128)



Features

- Quickly transforms a Type A-1 coupler into an adjustable blow gun
- Blow pressure easy to adjust by rotating spout
- Maximum inlet pressure 150 PSI

ADJUSTABLE POCKET BLOW GUN



Part No. 65.1017

♦ AVAILABLE IN STAINLESS STEEL 303

60 SCFM



Type A-2



One Way Shut-Off





PLUG
(STEEL)

**AUTOMATIC
COUPLER**
(STEEL/BRASS)



**MANUAL
COUPLER**
(STEEL/BRASS)

FEMALE THREAD





	Part No.	Part No.	Part No.
3/8" (F) NPT	17.2162	17.2762	17.2462

MALE THREAD



	Part No.	Part No.	Part No.
3/8" (M) NPT	17.2262	17.2862	17.2562

HOSE BARB



	Part No.	Part No.	Part No.
3/8" I.D.	17.2362	17.2962	17.2662

Applications

- Ideal for : Air tools
- Vacuum
- Water

Features

- Interchangeable with 3/8" ARO Type plugs
- Corrosion resistant

Specifications

Maximum Working Pressure

250 PSI

Working Temperature

-40°C to 107°C (-40°F to 225°F)

Air Flow

34 SCFM

Construction

Body : Steel
Sleeve and Valve Spring : Stainless Steel
Seal : Buna-N
Locking Balls : Stainless Steel
Socket Sleeve : Steel

**For any questions or information about
compressed air you may contact us at
Tel. : 1-888-730-0501 - Fax : 1-888-730-3522
or visit our web site at www.airmax.ca**