



### Features

- Differential pressure gauge
- Liquid level indicator
- Manual drain (ball valve)
- Maximum working pressure: 232 psig
- Maximum inlet temperature: 150°F

### HOUSING SPECIFICATIONS

CFM	NPT Port	Height	Width	Weight (lbs)*
35	1/2"	12-1/4"	4-1/8"	3.25
60	1"	15"	4-1/8"	3.60
100	1-1/2"	19-3/8"	5-1/2"	6.85
175	1-1/2"	19-3/8"	5-1/2"	6.85
255	1-1/2"	27-1/4"	5-1/2"	8.75
380	2"	29-5/8"	5-7/8"	8.80
500	2"	29-5/8"	5-7/8"	21.55

\* Including differential pressure gauge

### ACCESSORIES

Part No.	Description
58.1020	External Float Drain
11.2437K	External Timed Drain (120V)
58.1002	Liquid Level Indicator
58.1003	Differential Pressure Gauge



### FILTER GRADE

Description	09	07	05	03	01
Filter Type	Separator/filter	General Coalescing	Fine Coalescing	Extra-Fin Coalescing	Activated Carbon
Element Color	Yellow	White	Red	Blue	Green
Solid Filtration Grade [μ]	3	1	0.01	0.01	0.01
Oil Filtration [ppm w/w]	5	1	0.01	0.001	0.003
Max. Liquid Loading [ppm w/w]	20 000	1 000	60	40	n/a
Liquid Removal Efficiency	n/a	99.9%	99.9%	99.999%	n/a
Pressure Drop - Dry [psid]	1	1	1	2	1
Pressure Drop - Wet [psid]	2.5	2	3	5	n/a

### PART NO. - HOUSING & ELEMENTS

CFM	Housing	09	07	05	03	01
35	58.0016	58.0916	58.0716	58.0516	58.0316	58.0116
60	58.0020	58.0920	58.0720	58.0520	58.0320	58.0120
100	58.0024	58.0924	58.0724	58.0524	58.0324	58.0124
175	58.0028	58.0928	58.0728	58.0528	58.0328	58.0128
255	58.0032	58.0932	58.0732	58.0532	58.0332	58.0132
380	58.0036	58.0936	58.0736	58.0536	58.0336	58.0136
500	58.0040	58.0940	58.0740	58.0540	58.0340	58.0140

Part No.	CFM	NPT Port	Max. Liquid Loading	Liquid removal efficiency
58.2015	35	1/2"	20 000 ppm	95%
58.2025	60	3/4"	20 000 ppm	95%
58.2037	100	1"	20 000 ppm	95%
58.2055	175	1-1/4"	20 000 ppm	95%
58.2087	255	1-1/2"	20 000 ppm	95%
58.2140	380	2"	20 000 ppm	95%



For any questions  
or information about  
compressed air  
you may contact us at  
**Tel. : 1-888-730-0501**  
**Fax : 1-888-730-3522**  
or visit our web site at  
**[www.airmax.ca](http://www.airmax.ca)**